

crazy about

cutting tools

PRODUCTS OVERVIEW 2026

CENTERING
DRILLING
MILLING
DEBURRING



	ø - range [inch]	max. depth	Cooling		
			Int.	Ext.	
MIGU DRILL by Mikron Tool Centro		.020" – .236"	Chamfer 90°/120°	-	✓
CRAZY DRILL by Mikron Tool Twicenter		.012" – .394"	Chamfer 60°/90°/120°	✓	✓

Pilot and short drilling tools

MIGU DRILL 200		.004" – .059"	up to 2.4 x d	-	✓
CRAZY DRILL Flexpilot ^{STEEL}		.004" – .079"	3 x d	-	✓
CRAZY DRILL Flexpilot ^{TITANIUM}		.004" – .079"	3 x d	-	✓
CRAZY DRILL Pilot SST-Inox		.008" – .079"	3 x d Chamfer 90°	✓	✓
CRAZY DRILL Pilot		1/64" – 1/4"	2 x d Chamfer 90°	-	✓
CRAZY DRILL Crosspilot		1/64" – 1/4"	2 x d	-	✓
CRAZY DRILL Coolpilot		.039" – 1/4"	3 x d Chamfer 90°	✓	-
CRAZY DRILL Coolpilot Titanium ^{ATC}		.039" – 1/4"	3 x d Chamfer 90°	✓	-
CRAZY DRILL Hexalobe		.035" – .150" (T4 – T30)	up to 0.9 x d Chamfer 120°	-	✓
NEW CRAZY DRILL Hexalobe ^{FLAT}		.035" – .150" (T4 – T30)	up to 0.9 x d Chamfer 120°	-	✓

Drilling tools

MIGU DRILL 210		.004" – .118"	up to 8 x d	-	✓
CRAZY DRILL Steel		1/64" – 1/4"	4 x d 6 - 7 x d	-	✓
CRAZY DRILL SST-Inox		.008" – .079"	8 x d 12 x d	✓	✓
CRAZY DRILL Alu		.016" – .118"	5 x d 10 x d	-	✓
NEW CRAZY DRILL Titanium		.008" – .079"	3 x d 6 x d	✓	✓
CRAZY DRILL Cool		.030" – .236"	6 x d 10 x d 15 x d	✓	-
CRAZY DRILL Cool XL		.039" – .236"	15 x d, 20 x d, 30 x d	✓	-
CRAZY DRILL Cool SST-Inox		.039" – 1/4"	6xd, 10xd, 15xd, 20xd	✓	-
		.057" – 1/4"	30 x d		
		.079" – 1/4"	40 x d		
CRAZY DRILL Flex ^{STEEL}		.004" – .047"	20 x d, 30 x d	-	✓
		.012" – .079"	50 x d	✓	-
CRAZY DRILL Flex ^{TITANIUM}		.004" – .047"	30 x d	-	✓
		.012" – .047"	50 x d	✓	-
NEW CRAZY DRILL Flex ^{TITANIUM ATK}		.012" – .079"	30 x d 50 x d	✓	-
CRAZY DRILL Flex ^{SST-INOX}		.008" – .079"	30 x d	✓	-
		.012" – .079"	50 x d		
CRAZY DRILL Cool Titanium ^{ATC}		.039" – 1/4"	6 x d 10 x d	✓	-
CRAZY DRILL Cool Titanium ^{PTC}		.039" – 1/4"	3 x d 6 x d	✓	-

P	M	K	N	S ₁	S ₂		S ₃	H ₁	H ₂	Tool Book 2024 - 2027
Unalloyed and alloyed steel	Stainless steel	Cast iron	Non ferrous metals	Super alloys	Titanium Pure Alloyed		CrCo alloys	Hardened steel <55 HRC	Hardened steel ≥55 HRC	
○	○	○	○	⊗	○	○	⊗	○	⊗	p. 56
●	●	●	●	●	●	●	●	●	⊗	p. 68

○	⊗	○	○	⊗	⊗	⊗	⊗	○	⊗	p. 90
●	⊗	●	○	⊗	⊗	⊗	⊗	⊗	⊗	p. 108
⊗	⊗	⊗	○	⊗	●	●	⊗	⊗	⊗	p. 112
⊗	●	⊗	○	●	⊗	⊗	●	⊗	⊗	p. 118
●	○	●	●	⊗	●	●	⊗	●	⊗	p. 128
●	○	●	●	⊗	●	●	⊗	●	⊗	p. 140
⊗	●	⊗	⊗	●	⊗	⊗	●	⊗	⊗	p. 152
⊗	⊗	⊗	⊗	⊗	⊗	●	⊗	⊗	⊗	p. 162
⊗	●	⊗	⊗	⊗	●	●	●	⊗	⊗	p. 182
⊗	●	⊗	⊗	⊗	●	●	●	⊗	⊗	p. 183

○	⊗	○	○	⊗	⊗	⊗	⊗	○	⊗	p. 196
●	⊗	●	○	○	○	○	○	○	⊗	p. 210
⊗	●	⊗	○	●	⊗	⊗	●	⊗	⊗	p. 242
⊗	⊗	⊗	○	⊗	⊗	⊗	⊗	⊗	⊗	p. 226
⊗	⊗	⊗	⊗	⊗	●	●	⊗	⊗	⊗	*
●	○	●	○	○	○	○	○	●	⊗	p. 256
●	○	●	●	⊗	○	○	○	○	⊗	p. 282
⊗	●	⊗	⊗	●	⊗	⊗	●	⊗	⊗	p. 306
●	⊗	●	○	⊗	⊗	⊗	⊗	⊗	⊗	p. 371
⊗	⊗	⊗	○	⊗	●	○	⊗	⊗	⊗	p. 388
⊗	⊗	⊗	⊗	⊗	⊗	●	⊗	⊗	⊗	*
⊗	●	⊗	○	●	⊗	⊗	●	⊗	⊗	p. 396
⊗	⊗	⊗	⊗	⊗	⊗	●	⊗	⊗	⊗	p. 348
⊗	⊗	⊗	⊗	⊗	●	⊗	⊗	⊗	⊗	p. 352

Milling tools

	ø - range [mm]	max. depth	Cooling	
			Int.	Ext.
CRAZYMILL Cool Micro Z3-Z4	.008" – .039"	3 x d 5 x d	✓	-
CRAZYMILL Cool Z2	.012" – .14"	1.5 x d 3 x d 5 x d	✓	-
CRAZYMILL Cool Z4	.039" – .315"	2 x d 3 x d 4 x d 5 x d	✓	-
NEW CRAZYMILL Cool CF Chatter Free Z4-Z5	.039" – .315"	3 x d 4 x d	✓	-
NEW CRAZYMILL Cool SF Super finish Z5-Z6	.039" – .315"	3 x d 4 x d	✓	-
CRAZYMILL Hexalobe Hexalobe Z3-Z4	.008" – .039" (T4 – T30)	3.5 x d 5 x d	-	✓
CRAZYMILL Cool Plunge & Slot Z3	.039" – .315"	2.5 x d 5 x d	✓	-
CRAZYMILL Cool Ball Z2	.012" – .315"	2 x d 3 x d 5 x d	✓	-
CRAZYMILL Cool Ball Z4	.039" – .315"	2 x d 3 x d 3.5 x d 4.5 x d 5 x d	✓	-
NEW CRAZYMILL Knee Ball Z5-Z6-Z8	.236" – .315"	0.75 x d	✓	✓
NEW CRAZYMILL Knee Corner radius Z5	.236" – .315"	2 x d	✓	✓
NEW CRAZYMILL Knee Wiper	-	0.65 x d	✓	✓
NEW CRAZYMILL Knee Taper ball nose	.019" – .118"	-	✓	✓

Deburring tools

CRAZYMILL Frontchamfer 45° Frontchamfer	.039" – .236"	-	-	✓
CRAZYMILL Backchamfer 45° Backchamfer	.014" – .224"	3 x d 5 x d	-	✓
CRAZYMILL Doublechamfer 45°/45° Doublechamfer	.035" – .224"	3 x d 6 x d	-	✓
CRAZYMILL Radiuschamfer 300° Radiuschamfer	.039" – .236"	4 x d	-	✓
NEW CRAZYMILL Knee 45° Frontchamfer Z6	.078" – .236"	-	✓	✓

P	M	K	N	S ₁	S ₂		S ₃	H ₁	H ₂	Tool Book 2024 - 2027
					Titanium Pure	Titanium Alloyed				
Unalloyed and alloyed steel	Stainless steel	Cast iron	Non ferrous metals	Super alloys			CrCo alloys	Hardened steel <55 HRC	Hardened steel ≥55 HRC	
●	●	●	●	●	●	●	●	⊗	⊗	p. 418
●	●	●	●	●	●	●	●	●	⊗	p. 452
●	●	●	●	●	●	●	●	⊗	⊗	p. 478
●	●	●	●	●	●	●	●	⊗	⊗	*
●	●	●	●	●	●	●	●	⊗	⊗	*
⊗	●	⊗	⊗	⊗	●	●	●	⊗	⊗	p. 512
●	●	●	●	●	●	●	●	⊗	⊗	p. 526
●	●	●	●	●	●	●	●	●	⊗	p. 566
●	●	●	●	●	●	●	●	●	⊗	p. 594
⊗	⊗	⊗	⊗	⊗	⊗	⊗	●	⊗	⊗	*
⊗	⊗	⊗	⊗	⊗	⊗	⊗	●	⊗	⊗	*
⊗	⊗	⊗	⊗	⊗	⊗	⊗	●	⊗	⊗	*
⊗	⊗	⊗	⊗	⊗	⊗	⊗	●	⊗	⊗	*

●	●	●	●	●	●	●	●	●	⊗	p. 646
●	●	●	●	●	●	●	●	●	⊗	p. 647
●	●	●	●	●	●	●	●	●	⊗	p. 648
●	●	●	●	●	●	●	●	●	⊗	p. 649
⊗	⊗	⊗	⊗	⊗	⊗	⊗	●	⊗	⊗	*

* see dedicated brochures

RECOMMENDATION FOR USE

● Excellent | ● Good | ○ Acceptable | ⊗ Not recommended

Headquarter and Production
MIKRON SWITZERLAND AG, AGNO
Division Tool
Via Campagna 1
6982 Agno
Switzerland
Phone +41 91 610 40 00
mto@mikron.com

Production and Regrinding
MIKRON GERMANY GMBH
Abteilung Werkzeuge
Berner Feld 71
78628 Rottweil
Germany
Phone +49 741 5380 450
info.mtr@mikron.com


North and South America Sales
MIKRON CORP. MONROE
200 Main Street
Monroe, CT 06468
USA
Phone +1 203 261 3100
mmo@mikron.com

China Sales
MIKRON TOOL (SHANGHAI) CO., LTD.
Room A209, Building 3,
No. 526, 3rd East Fu te Road,
Shanghai, 200131
P. R. China
Phone +86 21 2076 5671
mtc@mikron.com
地址: 中国 (上海) 自由贸易试验区
中国上海市富特东三路526号3号楼第二层
A209室
邮编: 200131



www.mikrontool.com

Information and technical data are liable to changes without prior notification.
Mikron® is a trademark of Mikron Holding AG, Biel (Switzerland).



2.MKTG.00847 - 2026 - US